

Technical data sheet

CG860 HDMI AM/AM 2.1V- Support8K@60Hz ,4K@120Hz.

Version: A/0

【Product Picture】



【Product Description】

Model	
CG860	
Cable Length	
1m,1.5m,3m,5m,7.5m	
Outside diameter	
≤3m,OD:5.0mm;3-10m,OD:6.5mm	
Interface	
HDMI type A Male -HDMI type A Male	
Resolution	
8K@60Hz, 4K@120Hz, 2k@144Hz	
Audio	
eARC, Atoms, DTS Master, DTS:X	
HDR	
Dynamic HDR, Static HDR	
HDCP	
Supports HDCP 2.2	
Material	
Cable Shield Material	Aluminum-Mylar Foil with Braid
Conductor Gauge	23AWG
Conductor Material	Oxygen Free Copper

Technical data sheet

CG864 HDMI AM/AM 2.1V- Support 8K@60Hz ,4K@120Hz.

【Features】

- Fully compatible with HDMI eARC features for immersive audio support including Dolby Atmos and DTS X surround sound 7.1 and 5.1;
- Support HDR10, VRR ,Dynamic HDR and eARC;
- Supports HDCP 2.2,21:9 cinema aspect ratio,32 audio channels and a 1536 KHz sampling rate;
- Plug and play without driver dependent

【Application Environment】

Data transfer cable.

The interface connection cable is used to connect devices with an HDMI interface (digital signal) to devices with an HDMI interface (digital signal).

The HDMI Ethernet channel can be used to connect two or more HDMI-compatible devices with Internet connections of up to 100 Mbps.

The cable is suitable for PCs, workstations, server equipment, telecom networks and SCS networks.

