

Technical data sheet

D3752B DP-HDMI Active Optical Cable



Version: A/0

【 Product Picture】



【 Product Description】

Cable Length	
Up to 100m	
Interface	
Display port Male - HDMI Male	
Bandwidth	
Up to 18Gbps	
Resolution	
4k@60Hz	
Power	
No external power needed	
Mechanical / Condition	
Conductor Material	Optical
Insulation material	Polyethylene
Shield material	AL Foil shielding + Braided shielding
Shell Material	Aluminum

Technical data sheet

D3751 Display port 1.4V Active Optical Cable

【 Features】

Long-distance transmission, over 100 meters

Support up to 4k@60Hz 4:4:4/4:2:2/4:2:0. 4k60Hz 8bit 4:4:4,4k 30Hz 10bit 4:4:4, 1080P 16bit 4:4:4, and Perfectly compatible with HDMI v1.4 & v1.3 Standards

Support HDR/CEC/ EDID/ HDCP 2.2, 1536KHz Sample Rates,32 Uncompressed Audio and Video Sync,ARC, etc. Plug and play without driver dependent

Thinner, lighter, and softer than conventional copper cable

Highly resistant to EMI and RFI

No external power needed

【 Application Environment】

Data transfer cable.

Interface connection cable is designed to connect devices with DP connector (digital signal) to devices with DP connector (digital signal).

The scope of application of this cable is personal computers, workstations, server equipment, telecommunication networks, SCS networks.

【Attention】

1. When handling and setting up, do not let the fiber-optic cable be affected by great impact and side pressure, so that the shell itself will be deformed, which may cause the fiber to be stuck during the operation, and the resolution will be reduced. Even it caused worst interruption. Kindly use it in a properly way.
2. Check the appearance and performance of the optical fiber before installing the wiring, Please test the reconstruction on the equipment you need to use to avoid unnecessary trouble at the later stage.
3. When wiring, please be careful not to tie, or force to pull the fiber, or use feet and any other heavy objects to press the fiber, the process of breaking through the wall should not be more than 200N, if the fiber is broken, or the core was broken, the optical fiber can no longer be used.
4. The optical fiber should have a small amount of surplus at the turning point, make a good drop bend at the corner, and do not let the optical fiber touch sharp objects. the surplus optical fiber should be wound reasonably and beautifully. Also ensure a uniform force when winding the fiber. and the optical fiber should not be subjected to hard bending. So as not to damage the fiber.
5. When moving, use a line card to be fixed firmly, one at a distance of 1: 15 meters, do not stretch too much between fixed positions, leaving room for thermal expansion and cold shrinkage, and in addition, in order to prevent damage to the optical fiber in the vertical alignment, please stick a tape between the fixed-line cards .
6. For 4k video output with this HDMI Cable. please make sure your source devices and display devices both support 4K resolution also.
7. A friendly reminder: Please do not turn off your monitor, As the video and audio work at the same time. If monitor was turned off, the audio not work.