



Data cable.

The interface connection cable is designed to connect devices with an DVI connector (digital signal) to devices with an SVGA connector (analog signal).

The scope of application of this cable is personal computers, workstations, server equipment, telecommunication networks, SCS networks.

Technical Specifications

Physical Properties	
Model	TA491
Cable Length	0.2m
Interface	Input DVI (24+5) ,Male
	Output VGA (15 pin, High Density D-Sub), Female
Cable type	PVC jacket
Cable Shield Material	Aluminum-Mylar Foil with Braid
Conductor Gauge	30AWG
Conductor Material	Oxygen Free Copper
Cable Outer Dimension	6.0±0.2mm
Outer model	PVC molding
Color	Black
Performance	
Maximum Digital Resolutions	1080P@60Hz
OS Support	Works with Windows, Apple OS X, Chrome OS
Environmental	
Operating Temperature	-10°C to 50°C
Storage Temperature	-10°C to 50°C
Humidity	0%RH ~ 85%RH

Features

- Double shields effectively protect against EMI interference and provide more stable signal transmission.
- High purity Oxygen free copper inside ensures 0.01% transmission loss.
- VIDEO RESOLUTION SUPPORT on DVI to VGA adapter for up to HD 1080p including 800x600, 1024x768, 1280x1024, 1600x1200, 1680x1050; Audio must be transmitted separately on VGA to DVI cable
- DVI COMPATIBLE VGA to DVI adapter cable with 24+5 (29 pins) ports on a video graphics card with a single-link or dual-link DVI port; Check for the extra 4 pins on the port on your computer or display VGA port or DVI port
- Dual ferrite cores provides superior cable
- Thumb-tighten screws performance
- Plug and play, no drivers required.

Model List

TA491	Cable – adapter DVI (24+5)----> VGA , 0.2M
-------	--