



Data cable.

The interface connection cable is designed to connect devices with an DP connector (digital signal) to devices with an HDMI connector (digital signal).

The scope of application of this cable is personal computers, workstations, server equipment, telecommunication networks, SCS networks.

Technical Specifications

Physical Properties	
Model	TA561M-1.8M
Cable Length	1.8m
Interface	Input: DisplayPort (20 pin), Male
	Output: HDMI (19PIN) , MALE
Cable type	PVC jacket
Cable Shield Material	Aluminum-Mylar Foil with Braid
Conductor Gauge	24AWG
Conductor Material	Oxygen Free Copper
Cable Outer Dimension	5.5 ± 0.2mm
Outer model	ABS plastic shell+ PVC molding
Color	Black
Performance	
Maximum Digital Resolutions	4K@60HZ
OS Support	Works with Windows, Apple OS X, Chrome OS
Environmental	
Operating Temperature	-10°C to 50°C
Storage Temperature	-10°C to 50°C
Humidity	0%RH ~ 85%RH

Features

- Supports up to 4K@60HZ, including 2K@120HZ.
- Double shields effectively protect against EMI interference and provide more stable signal transmission.
- High purity Oxygen free copper inside ensures 0.01% transmission loss.
- Plug and play, no drivers required.

Model List

TA561M-1.8M	Cable DisplayPort M-> HDMI M 4K@60Hz 1.8m
-------------	---