



Cable for data transmission. This cable is used to connect the computer to a GSM modem or stationary modem to access the network. The scope of application of this cable is personal computers, workstations, server equipment, telecommunication networks, SCS networks.

Technical Specifications

Physical Properties	
Model	TC6911BK
Cable Length	1m,1.8m,3m
Interface	Input: 1x USB 2.0 Type-A Male
	Output: 1x USB 2.0 Mini-B 5pin Male
Connector Plating	Nickel-plated
Cable type	PVC jacket
Cable Shield Material	Aluminum-Mylar Foil
Conductor Gauge	30AWG
Conductor Material	Oxygen Free Copper
Cable Outer Dimension	4.0mm ±0.2mm
Outer model	PVC injection molding
Color	Black
Performance	
Data transfer	Up to 480Mbps,comply with USB Hi-Speed
OS Support	Works with Windows, MAC OS X, Chrome OS, Linux
Environmental	
Operating Temperature	-10°C to 50°C
Storage Temperature	-10°C to 50°C
Humidity	0%RH ~ 85%RH

Features

- Plug and play, no drive needed.
- The cable supports power delivery and data transfer at the same time.
- High purity Oxygen free copper inside ensure 0.01% transmission loss.
- Supports Hi-Speed USB 2.0 transfer rate at up to 480 Mbps.
- Use with any USB 2.0 rated device, backwards compatible with USB1.1 devices.

Model List

TC6911BK-1M	USB 2.0 A-->mini-B 5P (1m) , Telecom
TC6911BK-1.8M	USB 2.0 A-->mini-B 5P (1.8m) , Telecom
TC6911BK-3.0M	USB 2.0 A-->mini-B 5P (3m) , Telecom