Data cable.
The interface connection cable is designed to connect devices with an DP connector (digital signal) to devices with an DP connector (digital signal).

The scope of application of this cable is personal computers, workstations, server equipment, telecommunication networks, SCS networks.

Technical Specifications

Physical Properties	
Model	TCG865
Cable Length	1.0M, 1.5M, 2.0M, 3.0M.
Interface	Input DP 20PIN,Male
	Output DP 20PIN,Male
Cable type	PVC jacket
Cable Shield Material	Aluminum-Mylar Foil with Braid
Conductor Gauge	23AWG
Conductor Material	Oxygen Free Copper
Cable Outer Dimension	7.3±0.2mm
Outer model	PVC molding
Color	Black
Performance	
Maximum Digital Resolutions	16K@60, 8K@120
OS Support	Works with Windows, MAC OS X, Chrome OS
Environmental	
Operating Temperature	-10°C to 50°C
Storage Temperature	-10°C to 50°C
Humidity	0%RH ~ 85%RH

Features

- Supports up to Supports resolutions up to 16K@60HZ
- Double shields effectively protect against EMI interference and provide more stable signal transmission.
- High purity Oxygen free copper inside ensuress 0.01% transmission loss.
- With 2x ferrite cores, protected against electromagnetic interference.
- Plug and play, no drivers required.

Model List

TCG865-1.0M	Cable 2.1V DisplayPort M <--> Display Port M , 16K@60HZ
TCG865-1.5M	Cable 2.1V DisplayPort M <--> Display Port M , 16K@60HZ
TCG865-2.0M	Cable 2.1V DisplayPort M <--> Display Port M , 16K@60HZ
TCG865-3.0M	Cable 2.1V DisplayPort M <--> Display Port M , 16K@60HZ