



Cable for data transmission.

This cable is used to connect the computer to a GSM modem or stationary modem to access the network.

The scope of application of this cable is personal computers, workstations, server equipment, telecommunication networks, SCS networks.

Technical Specifications

Physical Properties	
Model	TUS709
Cable Length	0.3m,1m,1.8m
Interface	Input: USB 3.1 Type C, Male
	Output: USB 3.1 Type A, Male
Connector Plating	Nickel-plated
Cable type	PVC jacket
Cable Shield Material	Aluminum-Mylar Foil with Braid
Conductor Gauge	28+24AWG
Conductor Material	Oxygen Free Copper
Cable Outer Dimension	5.5mm ± 0.2mm
Outer model	PVC injection molding
Color	Black
Performance	
Data transfer	Up to 10Gbps
OS Support	Works with Windows, Apple OS X, Chrome OS, Linux, and Android.
Environmental	
Operating Temperature	-10°C to 50°C
Storage Temperature	-10°C to 50°C
Humidity	0%RH ~ 85%RH

Features

- Delivers up to 10Gbps high speed transaltion.
- Plug and play, no drive needed.
- Dual shields effectively protect against EMI interference and provide more stable signal transmission.
- High purity Oxygen free copper inside ensure 0.01% transmission loss
- Aluminum Alloy Casing,Have better heat dissipation and ultimate durability.than the PVC case.
- The cable is backward compatible with USB 3.0, USB 2.0,USB1.1 devices.

Model List

TUS709-0.3M	Cable USB3.1 Cm/Am 0.3m Telecom
TUS709-1M	Cable USB3.1 Cm/Am 1m Telecom
TUS709-1.8M	Cable USB3.1 Cm/Am 1.8m Telecom